

# UC – light V4 Drum

1H1/YXX/.../.../D/BAM XXXX-RIKUTEC / X. Revision

## Specification packaging materials data sheet

### Technical Data

Nominal volume	ca. 205 liter / approx. 54 gal.
Outer Diameter	ca. 581 mm / approx. 22.9 in.
Total height	ca. 955 mm / approx. 37.6 in.
Diameter filling opening	2 x S62 x 5mm
Weight	min. 11,0 kg / min. 24.2 lb



### Construction and description

Drum	<ul style="list-style-type: none"> <li>• manufactured by a coextrusion blow moulding process</li> <li>• Coex 2 Layer wall-design (HD PE)</li> <li>• Outer layer material: HD PE</li> <li>• Inner layer material: HD PE (virgin-no additives HD PE)</li> </ul>
Design	<ul style="list-style-type: none"> <li>• special designed L-Ring on the top</li> <li>• xxx kPA pressure rated</li> </ul>
Bungs	<ul style="list-style-type: none"> <li>• 1 x S62 x 5 air vent cap of HD PE with PTFE laminate</li> <li>• 1 x S62 x 5 cap of HD PE</li> </ul>
Closing torques	requirement corresponding to dip tube and seal selection

**Issued by/on**  
M. Monzel

**Revision status**  
25. Oct 2018/A